



PowAirBox II B - 230 V Conversion Kit

The PowAirBox II adapter kit contains both the power supply system for emergency vehicles with automatic ejection and an adapter that makes it easy to convert from a PowAirBox I to its more advanced successor.

- // Low installation depth (75 mm instead of 121 mm)
- // Sensor monitoring with start prevention
- // Wear-free automatic and manual ejection
- // Integrated undervoltage detector
- // Wear-free due to intelligent power electronics

The PowAirBox II, like its predecessor model, is a system for supplying power to emergency vehicles with automatic ejection.

The supply is effected via a special coupling. The robust housing is made of glass-fibre reinforced polyamide and has IP55 protection, making it dust-proof and splash-proof. Via indication integrated in the front of the PowAirBox II, the status of the feeding mains as well as the charging status of the batteries can be read easily and at any time. The integrated undervoltage detector alerts visually and acoustically in the event of a deep discharge of the vehicle battery.

The disconnection between the power supply and the automatic ejection of the coupling is monitored and controlled by a newly developed sensor technology and also works when operated manually via a touch sensor. As long as the coupling is not ejected, the start prevention is activated to provide maximum safety.

A superior multi-stage power control monitors the insertion and disconnection of the coupling and controls the connection and disconnection of the load. This optimises wear-free connection and disconnection even with particularly powerful inductive and capacitive loads.

Upgrade made easy thanks to total compatibility

The PowAirBox II is fully compatible with the previous version. Both the fit of the coupling and the mounting dimensions are unchanged, so vehicles can be easily upgraded to the PowAirBox II. A corresponding adapter makes the conversion uncomplicated. The low installation depth makes installation simple and flexible.

Product information sheet

Product number: 1101002006

Date: 19.12.2025

Page: 2/2



Technical Information

Compressed air	No*
Nominal voltage (supply unit)	230 V*
Adapter length	280 mm
Colour	Black
Contacts	L1/PE/N + 2x HK
Current (AC), max.	16 A
Installation depth	75 mm
International Protection (IP class)	IP55
Material	Polyamide
Nominal voltage (battery)	12 V / 24 V
Protection class	II
Status display	LED
Dimensions (L x W x H)	192 x 109 x 100.5 mm
Weight	1.2 kg

*In the chosen option