



Underfloor generator UF-15000

Compact, particularly quiet, smooth-running and powerful underfloor generator with a continuous output of 15 kVA/400 V or 7 kVA/230 V, dustproof and splash-proof to IP54 with 2-pole design for a fixed speed of 3,000 1/min.

- // Output voltage: 400 V/230 V
- // Rated power: 3-phase 15 kVA/1-phase 7 kVA
- // Rated current 22 A / 30 A
- // Protection class: IP54
- // Engine rpm for generator operation 1,350 1/min

Compact, particularly quiet, smooth-running and powerful underfloor generator with a continuous output of 15 kVA/400 V or 7 kVA/230 V, dustproof and splash-proof according to IP54. Different versions are available for different types of vehicles.

The underfloor generators are driven by a power take-off, are characterised by a high overload capacity and are maintenance-free. Specifically developed and tested mounting kits are available for many vehicles. On request, we supply underfloor generators as a complete set - including socket combinations and, if required, control cabinets according to DIN 14686.

Product information sheet

Product number: 0304073040

Date: 02.08.2025

Page: 2/2



Technical Information

| | |
|-------------------------------------|-------------|
| Generatordrehzahl | 3.000 1/min |
| International Protection (IP class) | IP54 |
| Polzahl | 2 |
| Rated Power (Alternating Current) | 7 kVA |
| Rated Power (three-phase current) | 15 kVA |
| Rated current (single-phase) | 30 A |
| Rated current (three-phase) | 22 A |
| Weight | 74 kg |

*In the chosen option