



Champ Charger 1207 (wet)

Small, compact and waterproof 12 V charger for universal use.

- // Compact design
- // Robust: metal housing
- // Waterproof: protection class IP67
- // Available for all lead-acid battery types

The Champ charger is suitable for charging 12 V wet batteries. With an output voltage of 12 V and a charging current of 7 A, the compact and lightweight charger ensures particularly gentle charging of the battery thanks to the pre-programmed charging characteristic curve.

Product information sheet

Product number: 0101033332

Date: 27.06.2026

Page: 2/2



Technical Information

| | |
|-------------------------------------|---------------------------------------|
| Cable length, AC input | 2.2 m* |
| Cable length, DC output | 1.5 m* |
| Charging current | 7 A* |
| Connection DC output | MagCode* |
| Connector, AC input | Schuko plug (type F)* |
| Input voltage (AC) | 230 V* |
| Output voltage (DC) | 12 V* |
| Type of battery | Lead acid (wet)* |
| Battery capacity | 55 Ah ... 170 Ah |
| Charging characteristic | IU1U2 charging characteristic, preset |
| Complies with DIN 14679:2024-02 | yes (except for output signal) |
| Input frequency range | 40 Hz ... 60 Hz |
| Input voltage range | 90 ... 270 V |
| International Protection (IP class) | IP67 |
| Level of efficiency | ? 88 % |
| Main charge | 14.1 V |
| Operating temperature | -30 °C ... +70 °C |
| Output voltage | 12 V |
| Protection class | I |
| Ripple | < 3 % |
| Switching frequency | 100 kHz |
| Trickle charge | 13.5 V |
| Dimensions (L x W x H) | 80 x 155 x 43 mm |
| Weight | 0.8 kg |

*In the chosen option