## Product information sheet

Product number: 0101043890

Date: 01.11.2025 Page: 1/2





## Champ Pro Charger 1230

Small, compact and waterproof 12 V charger for wet, gel, AGM and traction batteries with adjustable charging characteristic and power supply function.

- // Compact design
- // Power supply function
- // Robust housing
- // Waterproof according to IP67
- // For all lead-acid battery types

The 12 V charger of the Champ Pro type is an extremely robust built-in charger for the special vehicle sector. Due to the robust design with a sturdy metal housing and a fully encapsulated circuit board, all units in the series are waterproof and dustproof in accordance with protection class IP67.

In addition to the four adjustable charging characteristics, a microprocessor in combination with a temperature sensor integrated in the cable ensures the ideal charging voltage. This protects the battery and extends its service life.

The 30 A charging current is ideal for battery capacities from 90 Ah to 300 Ah. It almost doesn't matter which battery type is to be charged: Wet, gel and AGM lead batteries can be connected to the Champ Pro.

A state-of-charge indicator increases the user-friendliness. It can be read at any time how fully charged the battery already is.

## Product information sheet

Product number: 0101043890

**Date:** 01.11.2025 **Page:** 2/2



## **Technical Information**

Cable length, AC input	2 m*
Cable length, DC output	1.5 m*
Charging current	30 A*
Connection DC output	Ring terminal, M8*
Connector, AC input	Schuko plug (type F)*
Input voltage (AC)	230 V*
Output voltage (DC)	12 V*
Temperature sensor	Yes*
Balancing Charge	16 V
Battery capacity	90 Ah 300 Ah
Building main fuse	B16 A/C16 A
Charging characteristic	4 selectable charging programms
Complies with DIN 14679:2024-02	yes (except for output signal)
Input frequency range	40 Hz 60 Hz
Input voltage range	195 V 250 V
International Protection (IP class)	IP67
Level of efficiency	> 88 %
Main charge	14.2 V/14.4 V
Operating temperature	-30 °C +60 °C
Protection class	
Ripple	< 3 %
Trickle charge	13.6 V/13.8 V
Type of battery	Lead acid (wet, gel, AGM)/traction
Dimensions (L x W x H)	195 x 98 x 47 mm
Weight	1.5 kg
*In the chosen ention	

<sup>\*</sup>In the chosen option